

# GAS FILTERS, ALUMINIUM HOUSING, DN 15-50

## FT-SERIES

	Name of the parameter  Contamination indicator available	Housing material of gas filter	Nominal Diameter DN	Max. operating pressure, bar	Operating environment temperature, °C	Filtering pad operational area, sqm, min	Max. Filtering pad pores width, µm	Thread Diameter, inch	Max. dimensions length/width/height, mm	Max. weight, kg	Resistance factor
THREAD	FTA15A3(6)	Aluminium	15	3 (6)	-40 to +90	0,008	50	½	95/65/85	0,4	3,5
	FTA15B3(6)					0,013			95/65/140	0,58	3,4
	FTA15C3(6)					0,018			95/65/195	0,75	3,3
THREAD	FTA20A3(6)	Aluminium	20	3 (6)	-40 to +90	0,008	50	¾	95/65/85	0,4	3,1
	FTA20B3(6)					0,013			95/65/140	0,58	2,9
	FTA20C3(6)					0,018			95/65/195	0,75	2,7
THREAD	FTA25A3(6)	Aluminium	25	3 (6)	-40 to +90	0,010	50	1	105/75/95	0,53	3,1
	FTA25B3(6)					0,016			105/75/150	0,72	2,9
	FTA25C3(6)					0,023			105/75/205	0,92	2,7
THREAD	FTA32A3(6)	Aluminium	32	3 (6)	-40 to +90	0,030	50	1¼	140/100/180	2,8	3,3
	FTA40A3(6)		40						162/110/200	3,2	3,2
	FTA50A3(6)		50						162/120/190	3,4	3,4