

# GAS FILTERS, STEEL HOUSING, DN 15-65

## FT-SERIES

	Name of the parameter Contamination indicator available	Housing material of gas filter	Nominal Diameter DN	Max. operating pressure, bar	Operating environment temperature, °C	Filtering pad operational area, sqm, min	Max. Filtering pad pores width, µm	Thread Diameter, inch	Distance spacing on centers of the tapings/ diameter of the tapings, mm	Max. dimensions lenght/width/ height, mm	Max. weight, kg	Resistance factor
THREAD	FTS15A3(6)	Steel	15	3 (6)	-40 to +90	0,008	50	½	–	95/65/85	0,7	3,5
	FTS15B3(6)					0,013				95/65/140	0,88	3,4
	FTS15C3(6)					0,018				95/65/195	1,1	3,3
THREAD	FTS20A3(6)	Steel	20	3 (6)	-40 to +90	0,008	50	¾	–	95/65/85	0,7	3,1
	FTS20B3(6)					0,013				95/65/150	0,88	2,9
	FTS20C3(6)					0,018				95/65/205	1,1	2,7
FLANGE/THREAD	FTS25A3(6)	Steel	25	3 (6)	-40 to +90	0,010	50	1	–	105/75/95	0,83	3,1
	FTS25B3(6)					0,016				105/75/150	1,0	2,9
	FTS25C3(6)					0,023				105/75/205	1,2	2,7
	FTS25FA3(6)					0,034		–	75/11	160/100/150	3,1	3,5
FLANGE	FTS40FA3(6)	Steel	40	3 (6)	-40 to +90	0,04	50	–	100/14	210/160/200	7,0	2,5
	FTS50FA3(6)		50			0,05		–	110/14	240/160/215	14,5	2,8
	FTS65A3(6)		65			0,09		–	130/14	270/180/325	23	2,6